

SIROCCO

BREATH TAKING PERFORMANCE

SIROCCO-3s-216

SIROCCO-3s-216 is a 16 channel professional grade Network Video Recorder (NVR). It has a powerful embedded dual-core processor providing 5 megapixel resolution per channel and a global recording capacity of 128Mbps.

The SIROCCO-3s-216 is housed in a 1U desktop case with 2 internal SATA ports and 1 x 1GB network ports. It can facilitate 4 alarm inputs, 2 alarm outputs, HDMI and VGA video outputs. It supports backup methods via USB 3.0 and network.

The SIROCCO-3s-216 is provided license free, Onvif compatible and supports various 3rd party IP camera vendors.

PERFORMANCE

Resolution	IP	5 MegaPixel (1-25fps)
	HDCVI	Not applicable
	Analogue	Not applicable
IP Recording Processor		128Mbps Dual Core Embedded
Video Compression		H.264, MJPEG
Audio Compression		G711A



SOFTWARE

OS	Embedded Linux (ICR OS)
Video Detection	Motion Detection, Video Loss & Camera Masking
Smart Search	Yes
Simultaneous Playback	4 channel (3MP), 8 channel (720P), 16 channel (D1)
Max User Access	128
Network Functions	Alarm Server, DDNS, DHCP, DNS, Email, FTP, HTTP, IP Filter, IPv4, IPv6, PPPoE, RTSP, SMTP, TCP/IP, UDP, UPnP
IPC Support	Onvif, Axis, Bosch, Hikvision, Panasonic, Pelco, Samsung, Sony and many more...
Smart Phone / Tablet PC / Mac Software	ICRSS Pro & ICView SmartICRSS & Web Browser
Push Notifications	Yes
ICDDNS	Yes
Extra Stream	Yes
Onvif	Yes
Automation Integration	Yes
ARC Integration	Yes

CONNECTIVITY

Total Video Channels	16
IP Channels	16
HDCVI Channels	0
Analogue Channels	0
Audio (IP)	Yes
2 Way Audio	Yes
Alarm Inputs	4
Alarm Outputs	2
HDMI	1
VGA	1
BNC (Master)	0
BNC (Slave)	0
PoE IPC Ports	0
10/100M RJ45 Port	0
10/100/1000M RJ45 Port	1
RS-485	1
RS-232	1
USB 2.0 Port(s)	1 (Front)
USB 3.0 Port(s)	1 (Rear)

STORAGE

SATA Ports	2
RAID	n/a
eSATA Port	0
Backup Methods	USB & Network

ENVIRONMENTAL

Case Size	1U Desktop (375mm)
Dimensions (mm)	375 (W) x 285 (D) x 50 (H)
Power Supply	AC 100-240 V, 50/60 Hz
Power Consumption	20W (without HDD)
Working Environment	-10°C - +55°C / 10% - 90%RH / 86-106kpa
Weight	2KG (without HDD)
Certification	CE, FCC



• **European Head Office**
• IC Realtime,
• 12 Knockmitten Lane,
• Western Industrial Estate,
• Dublin 12,
• Ireland

• **UK Office**
• IC Realtime UK
• Surrey Technology Centre,
• 40 Occam Road,
• Guildford GU2 7YG,
• United Kingdom

• **USA Head Office**
• IC Realtime, LLC,
• 3050 N Andrews Ave EXT,
• Pompano Beach,
• FL 33064,
• USA

• **USA West Coast Office**
• IC Realtime West Coast,
• 14180 W Van Buren Street,
• Suite B-105, Goodyear,
• AZ 85338,
• USA